## (19) World Intellectual Property Organization International Bureau





(43) International Publication Date 23 September 2004 (23.09.2004)

PCT

## (10) International Publication Number WO 2004/080227 A1

(51) International Patent Classification<sup>7</sup>: A44C 27/00, 11/00, 5/02

(21) International Application Number:

PCT/IT2003/000144

(22) International Filing Date: 10 March 2003 (10.03.2003)

(25) Filing Language:

Italian

(26) Publication Language:

English

(71) Applicant (for all designated States except US): RAN-CANGELO DI RANCAN DARIO E PIETRO S.N.C. [IT/IT]; Via Lampertico Marzotto, 30, I-36070 Trissino (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): RANCAN, Pietro [IT/IT]; Via L. M. Marzotto, 32, I-36070 Trissino (IT).

(74) Agents: PAPA, Elisabetta et al.; Società Italiana Brevetti S.p.A., Piazza di Pietra, 39, I-00186 Rome (IT).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD FOR THE PRODUCTION OF ELONGATED ELEMENTS FOR JEWELS



[(57) Abstract Method for the production of elongated elements (1; 9; 13; 15) for making jewels, comprising the steps of: (a) providing a longitudinally hollow covering (2; 10) and a core (3; 7; 111, 112) placed within the covering (2; 10) and extending at crosswise opposite longitudinal edges of the covering (2; 10) and by the core (3; 7; 111, 112) to a pressing carried out at said longitudinal edges of the covering (2; 10).

WO 2004/080227 A1